

1/65




Fig. 1B

Fig. 1A

Fig. 1C




Fig. 1E

Fig. 2

Fig. 1D







Fig. 3

Fig. 4








6/65

Fig. 7






Fig. 8C




Fig. 9




Fig. 8B




Fig. 8E




Fig. 8A




Fig. 8D








Fig. 10A

Fig. 10B






Fig. 12




Fig. 13




Fig. 13

11/65

PRINTED CIRCUIT BOARD DETAIL




Fig. 14

12/65




Fig. 15A

13/65




Fig. 15B






Fig. 15D

14/65



15/65




Fig. 16

16/65

CIRCUIT DIAGRAM FOR RUBBER PLUG




Fig. 17




Fig. 18A




Fig. 18B




Fig. 18C




Fig. 18D

18/65

CIRCUIT DIAGRAM FOR "SPIDER"




Fig. 18E




Fig. 19B




Fig. 19D




Fig. 19A




Fig. 19C

20/65

CIRCUIT DIAGRAM FOR INDEPENDANT CIRCUIT ELEMENTS




Fig. 19E

21/65





Fig. 20B




Fig. 21A




Fig. 21B

21C




Fig. 21E




Fig. 21C




Fig. 21D




Fig. 21F

23/65




Fig. 22

24/65





Fig. 23

25/65



26/65




Fig. 25A




Fig. 25B




Fig. 25C

27/65




Fig. 26




Fig. 27

29/65




Fig. 28




Fig. 29




Fig. 30

32/65





Fig. 31



34/65




Fig. 32B




Fig. 32C

35/65




Fig. 32D

36/65




Fig. 33




Fig. 34

37/65




Fig. 35A




Fig. 35C




Fig. 35B




Fig. 35D




Fig. 35E

38/65




Fig. 35F




Fig. 35G




Fig. 35H

39/65




Fig. 36A











Fig. 36B

40/65



41/65



A, B, C, D, E, F, GND ARE CONNECTED TO A/D
CONVERTER CONNECTED TO COMPUTER

Fig. 39

42/65




Fig. 40A

ELASTOMERIC SENSING ELEMENT




Fig. 40B

43/65




Fig. 41

44/65




Fig. 43




Fig. 42

45/65




Fig. 44





Fig. 45


46/65



6-AXIS INPUT DEVICE

Fig. 46

47/65



CONNECTING PRINTED
CIRCUIT BOARD (TYP)

Fig. 48




Fig. 47

VOLTAGES AND PHASE ANGLES OF D,
E, AND F ARE A FUNCTION OF BALL
POSITION AND ORIENTATION, 565





Fig. 49B

111

0104 R500 P011110 10/511110

10/511110

49/65




Fig. 49C

50/65






Fig. 49D

51/65



52/65

Fig. 50B






Fig. 50C

54/65




Fig. 51A




Fig. 51B

55/65




Fig. 51C




Fig. 51D




Fig. 51E




Fig. 51F




Fig. 51G





Fig. 52

Fig. 53



58/65




Fig. 54A




Fig. 54B

59/65




Fig. 55

60/65




Fig. 56A

Fig. 56B





Fig. 56C



61/65




Fig. 57

10/511110


62/65

von Mises
1.862e+004
1.707e+004
1.552e+004
1.397e+004
1.241e+004
1.086e+004
9.310e+003
7.759e+003
6.207e+003
4.655e+003
3.104e+003
1.552e+003
8.235e+002

1 lbf
RADIAL FORCE

.040 WIDE
x .062 THICK
ELEMENTS

Fig. 58



Spring-Lateral-Force Static Nodal stress
Units psi Deformation Scale 1

10/511110

63/65

von Mises
2.631e+004
2.412e+004
2.193e+004
1.974e+004
1.754e+004
1.535e+004
1.316e+004
1.096e+004
8.771e+003
6.579e+003
4.386e+003
2.193e+003
1.113e+001

1 lbf
AXIAL FORCE




Fig. 59

Spring-Up-Force Static Nodal stress
Units psi Deformation Scale 1



64/65






Fig. 60

65/65



X+ Fig. 61A



X- Fig. 61B

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.